

Variable Message Sign Trailers



The versatility of aVMS Trailer means that it can be used for many different applications such as advance warning messages, traffic calming, speed radar advisory, real time programming and general advertising.

Variable Message Sign Trailers

Diverse Durable Available in a range of sizes and Fully galvanised trailer, powder display colour configurations. coated paint and solid state electronics throughout. Reliable Secure Yes, definitely! We have a proven Data encrypted and password protected. track record. **Cost Effective Easy to Program** Select from pre-programmed For long projects or multiple short term projects, cheaper messages or type a new message, click a button and you than hiring. are done. Local Sales Support **Remote Management** Remote management and GPS Local after sales support & spare location over cellular internet parts. connection with no additional software fee Warranty **Nation-wide Service** Branches in Brisbane, Sydney, 2 Year Limited Warranty. Melbourne, Adelaide and Townsville. **Australian Standard Local Management** Using on-board tablet PC. Built to Australian Standard 4852.2 - 2009. 1 - 3G modem option and telco data plan connection required.





Orders • Parts • Service • Support 1300 769 852

www.itsau.com.au

Variable Message Sign Trailers Specifications & Technical Data

iTS offers a range of LED VMS Trailers to suit all of your requirements. Our VMS trailers are suitable for road construction and maintenance, mines, traffic control, commercial and private use. The base trailer comes galvanised and powder coated as standard and can be customised with a number of upgrades which include cabinet and wheel locks, a speed radar for driver feedback, remote access programming and GPS for fleet tracking.







S Intelligent Traffic Systems

	SIZE A	SIZE B	SIZE C
Description:	Suitable for approaching vehicle speeds up to 60 km/h	Suitable for approaching vehicle speeds up to 90 km/h	Suitableforapproaching vehicle speeds greater than 90 km/h
Display Type:	Full matrix graphic Amber or 4 colour LED	Full matrix graphic Amber or 5 colour LED	Full matrix graphic Amber or 5 colour LED
Display Size:	1720mm x 1100mm	2440mm x 1400mm	2650mm x 1720mm
Power:	3 x 12V, 200AH deep cycle batteries	3 x 12V, 200AH deep cycle batteries	3 x 12V, 200AH deep cycle batteries
Solar Panels:	Amber = 2 x 150W panels Colour = 2 x 150W panels	Amber = 3 x 125W panels Colour = 3 x 125W panels	Amber = 3 x 125W panels Colour = 3 x 125W panels
Screen:	Anti-glare UV polycarbonate	Anti-glare UV polycarbonate	Anti-glare UV polycarbonate
Graphic:	Pre-programmed messages/ images with the ability to customise	Pre-programmed messages/ images with the ability to customise	Pre-programmed messages/ images with the ability to customise
Trailer Size: (L x W x H)	2.8m x 1.9m x 2.4m (with draw bar and fender)	3.3m x 1.8m x 2.4m (with draw bar and fender)	3.65m x 2.1m x 2.7m (with draw bar and fender)
Operating Height:	Adjustable up to 3400mm	Adjustable up to 3800mm	Adjustable up to 3800mm
Tare Weight:	700kg	800kg	900kg



iTS - Intelligent Traffic Systems 31 Boron Street, Sumner Park QLD 4074 / sales@itsau.com.au

1300 769 852 www.itsau.com.au

Orders • Parts • Service • Support