



	PCMS4880RC	PCMS548VT	PCMS320RC	PCMS320RTRC
Description:	Suitable for approaching vehicle speeds up to 50 km/h	Suitable for approaching vehicle speeds up to 60 km/h	Suitable for approaching vehicle speeds greater than 90 km/h	Suitable for approaching vehicle speeds greater than 90 km/h
Display Type:	Full matrix graphic HD Amber 1 LED per pixel	Full matrix graphic Amber 4 LEDs per pixel	Full matrix graphic Amber 4 LEDs per pixel	Full matrix graphic Colour 10 LEDs per pixel (4 red, 3 green, 3 blue)
Display Size:	946mm x 1422mm	1146mm x 2027mm	1605mm x 2497mm	1680mm x 2648mm
Characters:	Up to 8 lines of 20 (using 3x7) characters per line	Up to 3 lines of 12 characters per line	Up to 3 lines of 8 characters per line	Up to 3 lines of 8 characters per line
Solar Panels:	2 x 85W panels	2 x 85W panels	2 x 85W panels	3 x 85W panels
Batteries:	4 x 12V 33AH (AGM)	2 x 6V 225AH (AGM)	10 x 12V 33AH (AGM)	8 x 6V 180AH (AGM)
Overall Length:	1899mm	3565mm	3747mm	3829mm
Overall Width:	1487mm	1791mm	2096mm	2096mm
Axle/Suspension:	909kg	907kg	1588kg	1588kg
Travelling Height:	2356mm	2417mm	2754mm	2845mm
Operating Height:	Adjustable up to 4076mm	Adjustable up to 4081mm	Adjustable up to 4584mm	Adjustable up to 4705mm
Weight (approx.):	640kg	640kg	960kg	1080kg

